



Indoor Luminaire Photometric Data

Description Information

Luminary Name: 55252		Lum. Catalog:	Test ID:
Lamp Name:		Lamp Catalog:	Test Date: 2021/12/11
Manufacture:		Shld. Ang(°):	Test Machine:GON-2000
Test Lab:		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size(W*L*H):0.050m*-0.050m*0.000m		Lum. Area (m2):0.002	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp. (°C): 25	Humidity(%):


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 387.590	Luminary Flux(lm): 387.590	Field Angle(10%Imax): 31.1(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 386.476lm 99.71%
Rated Voltage(V):	Luminary EER(lm/W): 71.590	Up Lumens&Percent: 1.114lm 0.29%
Tested Power(W): 5.414	Max. Candela(cd): 3572.877	S/MH: C0_a180=0.250 C90_270=0.246
Lamps' Inside: 1	Max Cand@Ang. (°): C=210.0 γ=4.0	CIE Type: Semi-Direct
Tested Electrics(V, A, pf):24.0, 0.226	Beam Angle (50%Imax): 12.1(°)	ErP Φ use(90°): 375.893lm
Lamp Size(W*L*H):0.050m*-0.050m*0.000m	Left=-1.7°, Right=10.4°	IRF(%): 2401.168



2D Plane Light Intensity Distribution Curve


Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11



3D Light Intensity Distribution Modal

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11

3D Light Intensity Distribution Modal



Curves:

View Angles:

3D Model

Orient:0

Fixture

Tilt:0

Vert. HUD

Roll:0

Hori. HUD

Spin:0

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	2.46	2.46	0.64	0.64	47.0-48.0	1.33	367.96	0.34	94.94
1.0-2.0	7.22	9.69	1.86	2.50	48.0-49.0	1.27	369.23	0.33	95.26
2.0-3.0	11.52	21.21	2.97	5.47	49.0-50.0	1.22	370.45	0.31	95.58
3.0-4.0	15.16	36.36	3.91	9.38	50.0-51.0	1.16	371.61	0.30	95.88
4.0-5.0	18.04	54.40	4.65	14.04	51.0-52.0	1.10	372.71	0.28	96.16
5.0-6.0	20.08	74.47	5.18	19.21	52.0-53.0	1.05	373.75	0.27	96.43
6.0-7.0	21.19	95.67	5.47	24.68	53.0-54.0	0.99	374.75	0.26	96.69
7.0-8.0	21.33	117.00	5.50	30.19	54.0-55.0	0.94	375.68	0.24	96.93
8.0-9.0	20.50	137.49	5.29	35.47	55.0-56.0	0.89	376.57	0.23	97.16
9.0-10.0	18.98	156.47	4.90	40.37	56.0-57.0	0.84	377.41	0.22	97.37
10.0-11.0	17.26	173.73	4.45	44.82	57.0-58.0	0.78	378.19	0.20	97.57
11.0-12.0	15.73	189.46	4.06	48.88	58.0-59.0	0.73	378.92	0.19	97.76
12.0-13.0	14.45	203.91	3.73	52.61	59.0-60.0	0.68	379.61	0.18	97.94
13.0-14.0	13.31	217.22	3.43	56.04	60.0-61.0	0.64	380.25	0.16	98.10
14.0-15.0	12.26	229.47	3.16	59.21	61.0-62.0	0.60	380.84	0.15	98.26
15.0-16.0	11.27	240.75	2.91	62.11	62.0-63.0	0.56	381.40	0.14	98.40
16.0-17.0	10.36	251.11	2.67	64.79	63.0-64.0	0.52	381.92	0.13	98.54
17.0-18.0	9.52	260.63	2.46	67.24	64.0-65.0	0.48	382.40	0.12	98.66
18.0-19.0	8.76	269.39	2.26	69.50	65.0-66.0	0.45	382.84	0.12	98.78
19.0-20.0	8.07	277.46	2.08	71.59	66.0-67.0	0.42	383.26	0.11	98.88
20.0-21.0	7.46	284.92	1.92	73.51	67.0-68.0	0.39	383.65	0.10	98.98
21.0-22.0	6.89	291.81	1.78	75.29	68.0-69.0	0.36	384.00	0.09	99.07
22.0-23.0	6.36	298.17	1.64	76.93	69.0-70.0	0.33	384.34	0.09	99.16
23.0-24.0	5.86	304.03	1.51	78.44	70.0-71.0	0.31	384.64	0.08	99.24
24.0-25.0	5.38	309.41	1.39	79.83	71.0-72.0	0.28	384.92	0.07	99.31
25.0-26.0	4.95	314.36	1.28	81.11	72.0-73.0	0.25	385.18	0.07	99.38
26.0-27.0	4.55	318.91	1.17	82.28	73.0-74.0	0.23	385.41	0.06	99.44
27.0-28.0	4.20	323.11	1.08	83.36	74.0-75.0	0.20	385.61	0.05	99.49
28.0-29.0	3.89	327.00	1.00	84.37	75.0-76.0	0.18	385.79	0.05	99.54
29.0-30.0	3.60	330.60	0.93	85.30	76.0-77.0	0.15	385.94	0.04	99.57
30.0-31.0	3.34	333.94	0.86	86.16	77.0-78.0	0.13	386.07	0.03	99.61
31.0-32.0	3.10	337.04	0.80	86.96	78.0-79.0	0.10	386.17	0.03	99.63
32.0-33.0	2.89	339.92	0.74	87.70	79.0-80.0	0.08	386.25	0.02	99.65
33.0-34.0	2.69	342.61	0.69	88.40	80.0-81.0	0.06	386.31	0.02	99.67
34.0-35.0	2.52	345.13	0.65	89.05	81.0-82.0	0.05	386.36	0.01	99.68
35.0-36.0	2.36	347.49	0.61	89.65	82.0-83.0	0.04	386.39	0.01	99.69
36.0-37.0	2.21	349.70	0.57	90.22	83.0-84.0	0.03	386.42	0.01	99.70
37.0-38.0	2.08	351.77	0.54	90.76	84.0-85.0	0.02	386.44	0.01	99.70
38.0-39.0	1.96	353.74	0.51	91.27	85.0-86.0	0.01	386.46	0.00	99.71
39.0-40.0	1.87	355.61	0.48	91.75	86.0-87.0	0.01	386.47	0.00	99.71
40.0-41.0	1.78	357.39	0.46	92.21	87.0-88.0	0.01	386.47	0.00	99.71
41.0-42.0	1.70	359.09	0.44	92.65	88.0-89.0	0.00	386.47	0.00	99.71
42.0-43.0	1.63	360.72	0.42	93.07	89.0-90.0	0.00	386.48	0.00	99.71
43.0-44.0	1.57	362.29	0.40	93.47	90.0-91.0	0.00	386.48	0.00	99.71
44.0-45.0	1.51	363.80	0.39	93.86	91.0-92.0	0.00	386.48	0.00	99.71
45.0-46.0	1.45	365.24	0.37	94.23	92.0-93.0	0.00	386.48	0.00	99.71
46.0-47.0	1.39	366.63	0.36	94.59	93.0-94.0	0.00	386.48	0.00	99.71

IES Indoor Report


Photometric Filename:SL-T8-0600-A-15D.IES

Zonal Flux Tabulation - (Cont.)

Zone( γ )	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone( γ )	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	386.48	0.00	99.71	141.0-142.0	0.00	386.48	0.00	99.71
95.0-96.0	0.00	386.48	0.00	99.71	142.0-143.0	0.00	386.48	0.00	99.71
96.0-97.0	0.00	386.48	0.00	99.71	143.0-144.0	0.00	386.48	0.00	99.71
97.0-98.0	0.00	386.48	0.00	99.71	144.0-145.0	0.00	386.48	0.00	99.71
98.0-99.0	0.00	386.48	0.00	99.71	145.0-146.0	0.00	386.48	0.00	99.71
99.0-100.0	0.00	386.48	0.00	99.71	146.0-147.0	0.00	386.48	0.00	99.71
100.0-101.0	0.00	386.48	0.00	99.71	147.0-148.0	0.01	386.49	0.00	99.72
101.0-102.0	0.00	386.48	0.00	99.71	148.0-149.0	0.01	386.50	0.00	99.72
102.0-103.0	0.00	386.48	0.00	99.71	149.0-150.0	0.02	386.51	0.00	99.72
103.0-104.0	0.00	386.48	0.00	99.71	150.0-151.0	0.02	386.53	0.00	99.73
104.0-105.0	0.00	386.48	0.00	99.71	151.0-152.0	0.02	386.56	0.01	99.73
105.0-106.0	0.00	386.48	0.00	99.71	152.0-153.0	0.03	386.59	0.01	99.74
106.0-107.0	0.00	386.48	0.00	99.71	153.0-154.0	0.03	386.62	0.01	99.75
107.0-108.0	0.00	386.48	0.00	99.71	154.0-155.0	0.04	386.66	0.01	99.76
108.0-109.0	0.00	386.48	0.00	99.71	155.0-156.0	0.04	386.70	0.01	99.77
109.0-110.0	0.00	386.48	0.00	99.71	156.0-157.0	0.05	386.75	0.01	99.78
110.0-111.0	0.00	386.48	0.00	99.71	157.0-158.0	0.05	386.80	0.01	99.80
111.0-112.0	0.00	386.48	0.00	99.71	158.0-159.0	0.05	386.86	0.01	99.81
112.0-113.0	0.00	386.48	0.00	99.71	159.0-160.0	0.06	386.91	0.01	99.83
113.0-114.0	0.00	386.48	0.00	99.71	160.0-161.0	0.06	386.97	0.01	99.84
114.0-115.0	0.00	386.48	0.00	99.71	161.0-162.0	0.06	387.02	0.01	99.85
115.0-116.0	0.00	386.48	0.00	99.71	162.0-163.0	0.06	387.08	0.01	99.87
116.0-117.0	0.00	386.48	0.00	99.71	163.0-164.0	0.05	387.13	0.01	99.88
117.0-118.0	0.00	386.48	0.00	99.71	164.0-165.0	0.05	387.19	0.01	99.90
118.0-119.0	0.00	386.48	0.00	99.71	165.0-166.0	0.05	387.24	0.01	99.91
119.0-120.0	0.00	386.48	0.00	99.71	166.0-167.0	0.05	387.29	0.01	99.92
120.0-121.0	0.00	386.48	0.00	99.71	167.0-168.0	0.04	387.33	0.01	99.93
121.0-122.0	0.00	386.48	0.00	99.71	168.0-169.0	0.04	387.37	0.01	99.94
122.0-123.0	0.00	386.48	0.00	99.71	169.0-170.0	0.04	387.41	0.01	99.95
123.0-124.0	0.00	386.48	0.00	99.71	170.0-171.0	0.03	387.44	0.01	99.96
124.0-125.0	0.00	386.48	0.00	99.71	171.0-172.0	0.03	387.48	0.01	99.97
125.0-126.0	0.00	386.48	0.00	99.71	172.0-173.0	0.03	387.50	0.01	99.98
126.0-127.0	0.00	386.48	0.00	99.71	173.0-174.0	0.02	387.53	0.01	99.98
127.0-128.0	0.00	386.48	0.00	99.71	174.0-175.0	0.02	387.55	0.01	99.99
128.0-129.0	0.00	386.48	0.00	99.71	175.0-176.0	0.02	387.56	0.00	99.99
129.0-130.0	0.00	386.48	0.00	99.71	176.0-177.0	0.01	387.57	0.00	100.00
130.0-131.0	0.00	386.48	0.00	99.71	177.0-178.0	0.01	387.58	0.00	100.00
131.0-132.0	0.00	386.48	0.00	99.71	178.0-179.0	0.01	387.59	0.00	100.00
132.0-133.0	0.00	386.48	0.00	99.71	179.0-180.0	0.00	387.59	0.00	100.00
133.0-134.0	0.00	386.48	0.00	99.71					
134.0-135.0	0.00	386.48	0.00	99.71					
135.0-136.0	0.00	386.48	0.00	99.71					
136.0-137.0	0.00	386.48	0.00	99.71					
137.0-138.0	0.00	386.48	0.00	99.71					
138.0-139.0	0.00	386.48	0.00	99.71					
139.0-140.0	0.00	386.48	0.00	99.71					
140.0-141.0	0.00	386.48	0.00	99.71					

Rectangle ISO Lighting Intensity Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11




Maximum Light Intensity(cd): 3572.88  
Maximum Cand.@Angle: H=-3.5°,V=-2.0°

Plane ISO-Illuminance Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00  
Working Plane Maximum Illuminance(lx): 394.09  
Working Plane Maximum Illuminance Position(d/h):H-0.0 V-0.1

3D Plane ISO Illuminance Diagram

Lum. Name: 55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11

3D Plane Illuminance Modal






Space ISO Illuminance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:2590.08lx,0.0deg  
Plane Maximum Lighting Intensity and @Angle:2590.083cd,0eg

Illuminance-Distance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11



Indoor Luminance Limiting Curves

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	11443	9447	7167	5360	4094	3176	2113	0	0
C90	10851	8727	6515	4993	4091	3237	2113	337	0


Luminance Limiting Curve



Luminous Size: Length(m)=-0.050 Width(m)=-0.050 Height(m)=0.000 Area(m^2)=0.001963  
Luminous Type: Without Luminous Side  
Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11



Indoor Coefficient of Utilization Table

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11

Coefficients of Utilization – Zonal Cavity Method																					
Coef.	Effective Floor Cavity Reflectance RFC=0.20																				
RhoCC (%)	80				70				50				30				10				0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR	Coefficient of Utilization(%)																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95			
2	110	106	103	100	108	105	102	99	101	99	97	98	96	95	96	94	93	91			
3	106	101	97	94	104	100	96	93	97	94	92	95	92	90	93	91	89	87			
4	103	97	92	89	101	96	92	88	93	90	87	92	89	86	90	87	85	84			
5	99	93	88	85	98	92	88	85	90	87	84	89	85	83	87	84	82	81			
6	96	89	85	81	95	89	84	81	87	83	81	86	83	80	85	82	80	78			
7	93	86	82	79	92	86	81	78	84	81	78	83	80	78	82	79	77	76			
8	91	83	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74			
9	88	81	77	74	87	81	76	74	80	76	73	79	76	73	78	75	73	72			
10	86	79	74	72	85	78	74	72	78	74	71	77	74	71	76	73	71	70			

**Unified Glare Rating Table**

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2021/12/11

**Unified Glare Rating Table**

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	13.8	14.7	14.1	15.0	15.3	13.8	14.7	14.1	15.0	15.3
	Y=3H	14.1	14.9	14.5	15.2	15.6	14.1	14.9	14.5	15.2	15.6
	Y=4H	14.1	14.8	14.5	15.2	15.6	14.1	14.8	14.5	15.2	15.6
	Y=6H	14.0	14.7	14.4	15.1	15.5	14.0	14.7	14.4	15.1	15.5
	Y=8H	14.0	14.6	14.4	15.0	15.4	14.0	14.6	14.4	15.0	15.4
	Y=12H	13.9	14.5	14.3	14.9	15.3	13.9	14.5	14.3	14.9	15.3
X=4H	Y=2H	14.0	14.7	14.4	15.1	15.5	14.0	14.7	14.4	15.1	15.5
	Y=3H	14.4	15.0	14.8	15.4	15.8	14.4	15.0	14.8	15.4	15.8
	Y=4H	14.5	15.0	14.9	15.4	15.9	14.5	15.0	14.9	15.4	15.9
	Y=6H	14.4	14.8	14.9	15.3	15.8	14.4	14.8	14.9	15.3	15.8
	Y=8H	14.3	14.7	14.8	15.2	15.6	14.3	14.7	14.8	15.2	15.7
	Y=12H	14.2	14.6	14.7	15.1	15.6	14.3	14.6	14.8	15.1	15.6
X=8H	Y=4H	14.4	14.8	14.9	15.3	15.7	14.4	14.8	14.9	15.3	15.7
	Y=6H	14.3	14.6	14.8	15.1	15.6	14.3	14.6	14.9	15.1	15.7
	Y=8H	14.2	14.5	14.8	15.0	15.5	14.3	14.5	14.8	15.1	15.6
	Y=12H	14.2	14.4	14.7	14.9	15.5	14.2	14.4	14.7	14.9	15.5
X=12H	Y=4H	14.3	14.7	14.8	15.2	15.6	14.3	14.7	14.8	15.2	15.7
	Y=6H	14.2	14.5	14.8	15.0	15.5	14.3	14.5	14.8	15.0	15.6
	Y=8H	14.2	14.4	14.7	14.9	15.5	14.2	14.4	14.8	14.9	15.5
Variations with the objerver position at spacings											
S=1.0H		2.4/-4.8					1.9/-3.0				
S=1.5H		2.6/-4.5					2.5/-4.0				
S=2.0H		3.0/-4.8					2.7/-4.8				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.7					0.8				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

**IES Indoor Report**  
**Photometric Filename:SL-T8-0600-A-15D.IES**

## Candela Tabulation

V/H	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0	C300.0	C330.0
γ 0.0	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08	2590.08
γ 1.0	2194.95	2038.19	2106.88	2180.12	2450.67	2745.56	2966.57	3015.40	3043.53	2864.06	2663.79	2438.51
γ 2.0	1823.67	1656.23	1716.39	1845.79	2229.05	2739.37	3188.81	3340.63	3319.36	3037.39	2610.34	2178.92
γ 3.0	1508.77	1357.55	1408.25	1552.28	1974.63	2631.20	3274.26	3506.61	3441.79	3078.64	2470.82	1903.80
γ 4.0	1248.25	1128.10	1172.76	1305.67	1712.22	2455.34	3250.64	3572.88	3465.81	3011.36	2269.36	1629.76
γ 5.0	1047.31	951.28	987.71	1106.05	1460.68	2210.68	3133.45	3555.49	3403.96	2855.04	2018.52	1361.59
γ 6.0	888.77	806.31	837.17	935.69	1235.08	1916.54	2933.24	3452.21	3251.18	2626.23	1741.18	1125.61
γ 7.0	758.33	687.09	710.10	794.61	1041.12	1611.72	2649.48	3238.12	2988.80	2343.50	1456.90	944.03
γ 8.0	648.52	585.68	603.60	676.66	880.90	1325.54	2295.56	2896.36	2620.43	2015.12	1183.80	805.29
γ 9.0	554.34	499.16	513.83	579.98	749.76	1079.30	1890.72	2437.04	2192.01	1664.74	961.30	691.20
γ 10.0	473.90	426.88	439.81	498.47	640.29	891.68	1493.05	1952.68	1793.61	1340.52	803.33	594.90
γ 11.0	406.95	366.94	378.32	429.82	550.17	746.81	1171.67	1565.15	1478.65	1084.73	687.44	512.69
γ 12.0	351.71	316.41	326.80	372.52	474.47	632.55	951.59	1283.96	1234.21	911.30	593.57	441.32
γ 13.0	303.91	272.98	281.53	324.11	408.64	543.22	794.86	1070.07	1042.58	782.45	515.70	380.30
γ 14.0	263.42	236.35	243.62	282.10	353.36	470.14	675.98	895.42	885.20	672.67	447.95	330.18
γ 15.0	229.66	203.98	211.35	247.29	309.25	408.01	581.49	755.92	751.60	578.59	390.83	288.20
γ 16.0	200.32	174.91	184.22	216.26	272.31	355.06	502.48	640.88	639.72	497.47	341.08	252.39
γ 17.0	175.33	152.33	162.27	188.54	241.07	311.91	434.55	546.39	544.17	429.23	297.85	222.25
γ 18.0	152.70	133.92	143.12	165.79	214.71	275.36	377.04	469.07	462.78	370.30	261.77	195.74
γ 19.0	133.76	118.81	127.34	146.69	190.56	244.60	330.38	405.27	397.30	319.17	231.46	172.29
γ 20.0	117.67	106.18	113.74	130.52	169.32	219.25	291.06	351.86	342.74	277.54	204.55	152.21
γ 21.0	104.79	94.81	102.27	116.67	150.88	197.72	257.31	307.56	296.79	242.34	180.04	133.73
γ 22.0	93.58	85.04	92.65	103.92	134.78	178.38	228.61	269.40	257.43	211.88	158.46	117.04
γ 23.0	83.42	76.33	83.54	92.38	120.74	160.56	204.06	235.74	222.74	183.93	139.38	103.23
γ 24.0	73.97	68.99	74.97	82.32	108.70	143.56	181.49	206.76	194.08	159.69	121.87	91.53
γ 25.0	65.80	62.23	66.94	73.63	97.43	128.52	160.60	181.25	169.42	139.17	106.70	81.09
γ 26.0	58.90	55.79	59.85	66.10	87.07	115.39	142.15	158.91	148.48	122.43	94.52	71.84
γ 27.0	52.87	50.04	53.42	58.92	77.98	103.57	127.05	140.60	131.39	108.59	83.95	63.77
γ 28.0	47.81	45.19	47.93	52.44	69.67	92.80	113.89	125.03	117.54	96.79	74.66	56.66
γ 29.0	43.31	40.83	43.41	46.89	62.40	83.25	101.77	111.49	105.76	86.26	66.52	50.55
γ 30.0	39.49	37.17	39.91	41.91	55.72	74.44	91.11	99.87	95.09	77.06	59.32	45.52
γ 31.0	36.43	34.20	37.63	37.91	49.73	66.51	81.60	88.98	85.98	68.93	53.03	41.20
γ 32.0	33.70	31.69	35.26	34.59	44.42	59.20	72.94	79.30	77.56	62.20	47.78	37.73
γ 33.0	31.31	29.67	33.43	31.80	39.90	52.79	65.07	70.89	70.01	56.14	43.32	34.93
γ 34.0	29.28	27.82	30.72	29.59	36.24	47.41	57.96	63.41	62.82	50.77	39.56	32.59
γ 35.0	27.64	26.12	29.61	27.60	33.19	42.58	51.65	56.51	56.44	46.08	36.31	30.58
γ 36.0	26.09	24.91	27.32	25.82	30.66	38.29	46.09	50.26	50.48	42.07	33.51	28.82
γ 37.0	24.69	23.02	25.88	24.20	28.46	34.80	41.20	44.55	45.15	38.36	31.17	27.17
γ 38.0	23.33	21.79	24.23	22.79	26.58	31.99	37.08	39.78	40.74	35.05	29.16	25.62
γ 39.0	22.04	20.61	22.79	21.50	25.04	29.69	33.62	35.73	37.34	32.30	27.39	24.27
γ 40.0	20.78	19.26	21.48	20.29	23.66	27.76	30.85	32.45	34.80	29.94	25.89	23.04
γ 41.0	19.56	18.09	20.58	19.25	22.36	26.00	28.45	29.65	32.38	27.82	24.44	21.91
γ 42.0	18.49	17.09	19.18	18.06	21.14	24.51	26.47	27.16	30.15	25.95	23.15	20.84
γ 43.0	17.53	16.31	18.48	17.04	19.99	23.20	24.57	25.04	28.07	24.30	21.88	19.83
γ 44.0	16.68	15.61	17.40	16.03	18.91	22.09	22.86	23.35	26.49	22.80	20.77	18.84
γ 45.0	15.89	14.82	16.54	15.07	17.94	21.02	21.29	21.83	25.00	21.38	19.65	17.90
γ 46.0	15.12	13.99	15.63	14.22	16.98	19.97	19.95	20.39	23.56	20.10	18.53	17.02

IES Indoor Report

Photometric Filename:SL-T8-0600-A-15D.IES

---

Candela Tabulation - (Cont.)

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0	C210. 0	C240. 0	C270. 0	C300. 0	C330. 0
γ 47. 0	14. 32	13. 28	14. 68	13. 49	16. 14	18. 97	18. 69	19. 02	22. 01	19. 00	17. 56	16. 20
γ 48. 0	13. 51	12. 50	13. 68	12. 80	15. 30	17. 99	17. 48	17. 76	20. 70	17. 98	16. 63	15. 38
γ 49. 0	12. 73	11. 73	12. 72	11. 95	14. 50	17. 04	16. 38	16. 45	19. 60	16. 94	15. 83	14. 63
γ 50. 0	11. 92	10. 97	11. 73	11. 01	13. 69	16. 11	15. 22	15. 27	18. 58	15. 99	14. 98	13. 87
γ 51. 0	11. 05	10. 25	10. 90	10. 06	12. 84	15. 25	14. 07	14. 39	17. 56	15. 08	14. 18	13. 06
γ 52. 0	10. 25	9. 48	10. 11	9. 30	12. 00	14. 40	13. 21	13. 57	16. 75	14. 31	13. 41	12. 21
γ 53. 0	9. 47	8. 74	9. 34	8. 59	11. 14	13. 58	12. 45	12. 88	15. 89	13. 54	12. 68	11. 36
γ 54. 0	8. 70	8. 06	8. 43	7. 91	10. 31	12. 78	11. 73	12. 27	15. 05	12. 80	11. 90	10. 54
γ 55. 0	8. 07	7. 53	7. 77	7. 34	9. 50	11. 96	11. 01	11. 61	14. 21	12. 06	11. 05	9. 77
γ 56. 0	7. 49	7. 03	7. 21	6. 84	8. 72	11. 07	10. 34	10. 93	13. 36	11. 33	10. 22	9. 12
γ 57. 0	6. 92	6. 51	6. 70	6. 26	7. 95	10. 26	9. 65	10. 26	12. 58	10. 53	9. 47	8. 44
γ 58. 0	6. 32	5. 98	6. 28	5. 76	7. 29	9. 48	8. 94	9. 60	11. 77	9. 76	8. 71	7. 83
γ 59. 0	5. 72	5. 61	5. 88	5. 30	6. 64	8. 72	8. 25	8. 92	10. 97	9. 09	7. 92	7. 29
γ 60. 0	5. 26	5. 21	5. 45	4. 90	6. 04	8. 05	7. 63	8. 27	10. 22	8. 34	7. 26	6. 80
γ 61. 0	4. 84	4. 86	5. 05	4. 52	5. 59	7. 43	7. 05	7. 65	9. 45	7. 63	6. 68	6. 35
γ 62. 0	4. 44	4. 55	4. 68	4. 22	5. 16	6. 88	6. 52	7. 10	8. 71	7. 09	6. 12	5. 87
γ 63. 0	4. 07	4. 18	4. 37	3. 91	4. 76	6. 33	5. 99	6. 57	8. 13	6. 56	5. 60	5. 42
γ 64. 0	3. 72	3. 88	4. 04	3. 65	4. 41	5. 86	5. 49	6. 07	7. 53	5. 99	5. 14	4. 99
γ 65. 0	3. 40	3. 53	3. 73	3. 39	4. 07	5. 42	5. 08	5. 64	6. 93	5. 48	4. 72	4. 60
γ 66. 0	3. 09	3. 19	3. 44	3. 14	3. 75	5. 02	4. 70	5. 25	6. 45	5. 05	4. 36	4. 25
γ 67. 0	2. 82	2. 85	3. 16	2. 88	3. 44	4. 63	4. 35	4. 86	6. 04	4. 67	4. 01	3. 90
γ 68. 0	2. 56	2. 58	2. 85	2. 61	3. 17	4. 27	4. 05	4. 49	5. 64	4. 35	3. 70	3. 57
γ 69. 0	2. 35	2. 28	2. 59	2. 39	2. 90	3. 92	3. 77	4. 19	5. 28	4. 06	3. 40	3. 25
γ 70. 0	2. 13	2. 01	2. 32	2. 17	2. 66	3. 59	3. 51	3. 93	4. 95	3. 80	3. 11	2. 95
γ 71. 0	1. 90	1. 76	2. 07	1. 92	2. 40	3. 25	3. 26	3. 66	4. 65	3. 53	2. 82	2. 64
γ 72. 0	1. 68	1. 51	1. 81	1. 71	2. 15	2. 93	3. 01	3. 39	4. 35	3. 27	2. 55	2. 35
γ 73. 0	1. 49	1. 29	1. 59	1. 50	1. 91	2. 62	2. 77	3. 15	4. 06	3. 02	2. 32	2. 06
γ 74. 0	1. 29	1. 08	1. 38	1. 28	1. 68	2. 32	2. 51	2. 90	3. 76	2. 78	2. 05	1. 77
γ 75. 0	1. 07	0. 88	1. 14	1. 07	1. 40	1. 99	2. 19	2. 67	3. 48	2. 54	1. 78	1. 49
γ 76. 0	0. 86	0. 70	0. 94	0. 87	1. 08	1. 70	1. 88	2. 43	3. 22	2. 29	1. 33	1. 22
γ 77. 0	0. 64	0. 51	0. 71	0. 69	0. 83	1. 40	1. 62	2. 20	2. 93	2. 05	1. 02	0. 96
γ 78. 0	0. 38	0. 31	0. 50	0. 51	0. 62	1. 05	1. 36	1. 99	2. 66	1. 83	0. 76	0. 69
γ 79. 0	0. 11	0. 12	0. 31	0. 29	0. 45	0. 78	1. 15	1. 76	2. 40	1. 61	0. 59	0. 43
γ 80. 0	0. 00	0. 00	0. 13	0. 12	0. 30	0. 49	0. 97	1. 55	2. 12	1. 39	0. 43	0. 15
γ 81. 0	0. 00	0. 00	0. 00	0. 00	0. 14	0. 24	0. 79	1. 34	1. 89	1. 18	0. 29	0. 00
γ 82. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 62	1. 13	1. 62	0. 97	0. 13	0. 00
γ 83. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 45	0. 93	1. 40	0. 76	0. 00	0. 00
γ 84. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 29	0. 73	1. 14	0. 57	0. 00	0. 00
γ 85. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 12	0. 52	0. 93	0. 39	0. 00	0. 00
γ 86. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 35	0. 74	0. 19	0. 00	0. 00
γ 87. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 17	0. 54	0. 03	0. 00	0. 00
γ 88. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 02	0. 37	0. 00	0. 00	0. 00
γ 89. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 23	0. 00	0. 00	0. 00
γ 90. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 10	0. 00	0. 00	0. 00
γ 91. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 01	0. 00	0. 00	0. 00
γ 92. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00
γ 93. 0	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00	0. 00





Candela Tabulation - (Cont.)

V/H	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0	C300.0	C330.0
γ 141.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 144.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 146.0	0.11	0.18	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03
γ 147.0	0.27	0.36	0.23	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.16
γ 148.0	0.42	0.54	0.41	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.31
γ 149.0	0.59	0.70	0.59	0.28	0.00	0.00	0.00	0.00	0.00	0.00	0.12	0.46
γ 150.0	0.74	0.87	0.76	0.44	0.06	0.00	0.00	0.00	0.00	0.00	0.26	0.60
γ 151.0	0.89	1.02	0.94	0.61	0.20	0.00	0.00	0.00	0.00	0.02	0.41	0.75
γ 152.0	1.03	1.18	1.11	0.77	0.36	0.01	0.00	0.00	0.00	0.19	0.58	0.88
γ 153.0	1.16	1.32	1.24	0.93	0.50	0.16	0.02	0.00	0.05	0.35	0.72	1.02
γ 154.0	1.29	1.41	1.37	1.08	0.65	0.29	0.17	0.09	0.24	0.51	0.87	1.15
γ 155.0	1.39	1.52	1.47	1.22	0.81	0.46	0.32	0.25	0.41	0.69	1.01	1.27
γ 156.0	1.50	1.61	1.57	1.34	0.96	0.61	0.49	0.43	0.60	0.84	1.15	1.38
γ 157.0	1.58	1.69	1.65	1.46	1.09	0.76	0.65	0.61	0.78	0.99	1.26	1.50
γ 158.0	1.66	1.75	1.72	1.57	1.24	0.91	0.81	0.78	0.94	1.14	1.39	1.57
γ 159.0	1.72	1.80	1.79	1.65	1.35	1.04	0.95	0.95	1.11	1.27	1.48	1.65
γ 160.0	1.77	1.85	1.84	1.73	1.46	1.18	1.10	1.10	1.24	1.38	1.56	1.73
γ 161.0	1.80	1.88	1.88	1.79	1.56	1.31	1.24	1.23	1.37	1.48	1.64	1.76
γ 162.0	1.85	1.92	1.94	1.85	1.64	1.43	1.37	1.37	1.47	1.57	1.71	1.81
γ 163.0	1.86	1.95	1.97	1.90	1.71	1.52	1.48	1.47	1.56	1.64	1.77	1.85
γ 164.0	1.87	1.97	1.99	1.95	1.77	1.62	1.57	1.56	1.63	1.70	1.80	1.87
γ 165.0	1.87	1.98	2.02	1.97	1.83	1.70	1.65	1.63	1.70	1.74	1.84	1.89
γ 166.0	1.86	1.99	2.02	2.00	1.88	1.77	1.72	1.71	1.74	1.77	1.86	1.90
γ 167.0	1.85	1.99	2.04	2.01	1.91	1.83	1.77	1.77	1.78	1.82	1.87	1.89
γ 168.0	1.82	1.97	2.04	2.02	1.94	1.88	1.82	1.79	1.80	1.83	1.88	1.89
γ 169.0	1.78	1.95	2.02	2.01	1.95	1.92	1.85	1.84	1.85	1.85	1.90	1.88
γ 170.0	1.76	1.93	2.00	2.00	1.98	1.94	1.88	1.87	1.86	1.87	1.89	1.87
γ 171.0	1.71	1.89	1.97	1.98	1.97	1.98	1.90	1.88	1.87	1.88	1.90	1.85
γ 172.0	1.69	1.85	1.94	1.96	1.98	1.98	1.91	1.90	1.88	1.88	1.90	1.86
γ 173.0	1.67	1.81	1.90	1.93	1.97	1.99	1.92	1.91	1.90	1.90	1.90	1.85
γ 174.0	1.66	1.78	1.86	1.91	1.96	1.99	1.90	1.92	1.91	1.91	1.90	1.86
γ 175.0	1.65	1.76	1.84	1.90	1.94	1.98	1.88	1.92	1.92	1.92	1.91	1.85
γ 176.0	1.67	1.75	1.82	1.89	1.95	1.98	1.85	1.93	1.93	1.93	1.92	1.87
γ 177.0	1.69	1.75	1.82	1.90	1.95	1.96	1.84	1.92	1.94	1.96	1.93	1.90
γ 178.0	1.71	1.79	1.83	1.91	1.95	1.96	1.83	1.90	1.94	1.94	1.95	1.92
γ 179.0	1.75	1.81	1.87	1.92	1.95	1.96	1.81	1.87	1.93	1.96	1.95	1.95
γ 180.0	1.88	1.88	1.88	1.88	1.88	1.88	1.88	1.88	1.88	1.88	1.88	1.88