



LED Flood Light

Installation Instructions





Single Module





Double Module



Physical Dimensions(Unit: mm/inch)




Single module




Double module


CCT + Power Selectable




Slipfitter Mount(Unit: mm/inch)




1. ✕



2. ✕




Single module




Double Module

3. ✕




Single module





Double module

4. ✕




Single Module




Double Module

5. ✕






Single Module

6. ✕




Double Module




Yoke Mount(Unit: mm/inch)



Single Module





Double Module





1. ✖ Single Module




Double Module




2. ✖ Single Module




Double Module




2. ✖ Single Module




Double Module






Wall Mount(Unit: mm/inch)



1. ✖



2. ✖



Product Specifications	75W	100W	120W	150W	200W	240W	300W
Input Voltage	100-277V AC / 120-277 VAC / 100-240 VAC / 220-240 VAC (Subject to the input voltage on nameplate)						
Power Frequency	50 / 60Hz						
Outlook Dimensions	233x187x141mm(9.17"x7.4"x5.6")				469x187x185mm(18.5"x7.4"x7.3")		
Luminaire Net Weight	3.4±0.3kg(7.48±0.66Lbs)				7.9±0.3kg(17.38±0.66Lbs)		
Projected Area	0.03m²(0.43ft²)				0.07m²(0.86ft²)		
Working Temperature	-30°C to +50°C(-22°F to +122°F)						
Storing Temperature	-40°C to +70°C(-40°F to +158°F)						

Dimmable

DIM+/DA1 DIM-/DA2						
DIM+/DA1 DIM-/DA2 Aux 12Vdc +						
DIM+/DA1 DIM-/DA2 Aux 12Vdc -						
L N ⊕ GND						



Warning! Do not wire dim cord to high voltage, or dim function will fail.

- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.
- For type Y attachments:
if the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.