PENDANT35-R

MAGNETIC TRACK SERIES













SAOMAX

DISTRIBUTION

20°
302 30
30°

563 Ф0.69 Ф1.03 90 Ф1.55

30-
30° 30°
40°

(m)	E(lx)	Φ(m)
1	2519	Ф0.32
2	629	Ф0.65
3	279	Ф0.98
4	157	Ф1.31
5	100	Ф1.64



h(m)	E(Ix)	Φ(m)
2	278	Ф0.96
3	124	Ф1.44
3.5	91	Ф1.68
4	69	Ф1.92
5	44	Ф2.40
n(m)	E(lx)	Φ(m)



E(Ix)	Ф(т)
799	Ф0.75
199	Φ1.51
88	Ф2.27
49	Ф3.02
31	Ф3.78
	799 199 88 49

SPECIFICATIONS

01 2011 107 (110140		
Model No.	Pendant35-R	
Power Consumption(±10%)	5W	
Input Voltage	24VDC	
Driver Type	Constant Current (CC)	
Dimming	Yes	
Luminous Flux (±10%)	440	
Efficacy(4000K Ra70)	88lm/W	
Correlated Color Temperature	4000K (2700, 3000K, 5000K optional)	
Color Rendering Index	Ra80 (Ra90 optional)	
Beam Angle	20°, 30°, 40°, 60°	
UGR level	NA	
Mounting Option	Track Mounted/Ceiling Pendant	
Material	Aluminum Alloy Body, Polycarbonate Optical Lens	
Finish	Powder Coating	
Fixture Color	Black/White/Gold/Bronze	
EPA	NA	
IK Rating	NA	
IP Rating	IP20	
Life Time of LED @Ta=25°C	50000 Hours	
Warranty	5 Years	
Application	Residential, Retail, Office, etc.	

DIMENSIONS





