

SPOT35-T

MAGNETIC TRACK SERIES




SPECIFICATIONS

Model No.	Spot35-T
Power Consumption(±10%)	2x5W
Input Voltage	24VDC
Driver Type	Constant Current (CC)
Dimming	Yes
Luminous Flux (±10%)	880lm
Efficacy(4000K Ra70)	88lm/W
Correlated Color Temperature	4000K (2700, 3000K, 5000K optional)
Color Rendering Index	Ra80 (Ra90 optional)
Beam Angle	20°, 30°, 40°, 60°
UGR level	NA
Mounting Option	Track Mounted
Material	Aluminum Alloy Body, Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Color	Black/White/Gold
IP Rating	IP20
Life Time of LED @Ta=25°C	50000 Hours
Warranty	5 Years
Application	Residential, Retail, Office, etc.

DISTRIBUTION


3000K 80Ra

20°




h(m)	E(k)	Φ(m)
2	563	Φ0.69
3	250	Φ1.03
3.5	183	Φ1.20
4	140	Φ1.38
5	90	Φ1.55

30°




h(m)	E(k)	Φ(m)
1	2519	Φ0.32
2	629	Φ0.65
3	279	Φ0.98
4	157	Φ1.31
5	100	Φ1.64

40°




h(m)	E(k)	Φ(m)
2	278	Φ0.96
3	124	Φ1.44
3.5	91	Φ1.68
4	69	Φ1.92
5	44	Φ2.40

60°




h(m)	E(k)	Φ(m)
1	799	Φ0.75
2	199	Φ1.51
3	88	Φ2.27
4	49	Φ3.02
5	31	Φ3.78

TRACK ADAPTERS



Senior



Curvy

