

SPOT70

MAGNETIC TRACK SERIES




SPECIFICATIONS

Model No.	Spot70
Power Consumption(±10%)	20W
Input Voltage	24VDC
Driver Type	Constant Current (CC)
Dimming	Yes
Luminous Flux (±10%)	1450lm
Efficacy(4000K Ra70)	73lm/W
Correlated Color Temperature	4000K (2700, 3000K, 5000K optional)
Color Rendering Index	Ra80 (Ra90 optional)
Beam Angle	15°, 24°, 36°
UGR level	NA
Mounting Option	Track Mounted
Material	Aluminum Alloy Body, Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Color	Black/White
IP Rating	IP20
Life Time of LED @Ta=25°C	50000 Hours
Warranty	5 Years
Application	Residential, Retail, Office, etc.

DISTRIBUTION


3000K 80Ra

15°




h(m)	E(lx)	Φ(m)
1	8050	Φ0.31
2	2012	Φ0.63
3	894	Φ0.95
4	503	Φ1.27
5	322	Φ1.59

24°




h(m)	E(lx)	Φ(m)
1	5787	Φ0.47
2	1447	Φ0.95
3	643	Φ1.42
4	361	Φ1.90
5	231	Φ2.37

36°




h(m)	E(lx)	Φ(m)
1	3344	Φ0.72
2	836	Φ1.44
3	371	Φ2.17
4	209	Φ2.89
5	133	Φ3.61


TRACK ADAPTERS



Senior



Junior



Curvy

